



WORLD CLASS LUBRICANTS

## TECHNICAL DATA SHEET

**PRODUCT** **INDY GREASE LX3**  
Lithium Complex Grease

### DESCRIPTION

INDY Grease LX3 is lead free, extremely shear stable and offers a higher than average operating temperature. It is blended from high quality solvent refined oils and incorporates an extreme pressure additive as well as corrosion- and oxidation inhibitors.

### APPLICATION

INDY Grease LX3 has excellent load carrying abilities and resists water action. This grease is designed for a wide variety of service operating conditions to extend service life in heavy duty applications. It is suitable for use in all types of bearings, CV joints, universal joints, gears, cams, lift trucks, plant vehicles and general machinery.

### TECHNICAL CHARACTERISTICS

<b>Consistency NLGI</b>		<b>3</b>
Soap Type		Lithium Complex
Dropping Point	°C	230 min
Worked Penetration @ 25°C	mm	220-250
Water Washout @ 38°C	%	3 max
Recommended operating temperature	°C	-30 to 160
Appearance	visual	Brown
Timken oil load	kg	27
Viscosity @ 40°C	cSt	200

### PACK SIZES

180 kg / 15 kg / 4.5 kg

Revision 5: 09 April 2021

Durban Head Office: + 27 31 910 3111  
+ 27 60 572 8088

Pietermaritzburg: + 27 33 392 9300  
+27 33 390 1844

Based on available information, this product is not expected to produce harmful effects to health when used for the intended application. MSDS are available on request or via the internet. Used oil is potentially hazardous to your health and the environment. Dispose of used oil correctly and according to legislation.